

# PRODUCT DATASHEET SP RING D100 BK

SPOT RING | Refurbishment rings to reduce existing cut-out in recessed ceilings

#### Areas of application

- Refurbishment of existing cut-outs in recessed ceilings



#### Product benefits

- Retrofit: Replacement of old recessed lights with LEDVANCE SPOTs FIX or ADJ in latest LED-technology
- Standardize: Reduce existing cut-outs to a standard cut-out of 68 mm
- Versatile: Refurbishment rings for padding cut-out holes from Ø68 Ø90 or Ø68 Ø115 or Ø115 Ø160 mm

#### Product features


- Material: deep-drawn steel
- Suitable only for LEDVANCE SPOTs in 68 mm cut-out
- Silicon-pad protected springs



## TECHNICAL DATA

# Dimensions & Weight

Diameter	100 mm
Height	4 mm
Product weight	50.00 g



SP RING D100

## Materials & Colors

Product color	Black
RAL Color (most similar)	RAL 9004
Body material	Steel

# Application & Mounting

Ambient temperature range	-20+40 °C
Mounting type	Recessed
Mounting location	Ceiling
Mounting diameter	6890 mm
Replaceable light source	No

## DOWNLOAD DATA

	Documents and certificates	Document name
POF	User instruction / safety instructions	UI SP FIX P and SP FIX ADJ
POF	User instruction / safety instructions	UI SP DK FIX P

	Documents and certificates	Document name
POF	User instruction / safety instructions	UI SP AIR FIX P
	Tender texts	Document name
	Tender documents	SPOT RING D100 BK-EN

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854136542	BAG 1	180 mm x 160 mm x 1 mm	51.00 g	0.03 dm <sup>3</sup>
4099854136559	Shipping box 20	114 mm x 114 mm x 72 mm	1065.00 g	0.94 dm <sup>3</sup>
4099854136566	Shipping box 240	355 mm x 240 mm x 164 mm	13084.00 g	13.97 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.