

PRODUCT DATASHEET SMART+ CLOUD CAMERA

Smart+ Camera Cloud | Outdoor Smart Camera Cloud



Areas of application

- Outdoor use (IP44)
- Garages
- Entrance areas

Product benefits

- Easy and quick installation
- Increased perception of safety thanks to high brightness
- The recorded data is saved on the unit's memory card or cloud storage
- High-quality materials

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Built in speaker and alarm siren
- Color temperature: 3,000 K (Warm White)
- Network protocol: WiFi
- Type of protection: IP44
- HD Live view camera
- 3 MP camera
- Talk from mobile phone to camera



- Automatic night mode
- Motion sensor with activity schedule
- Auto record of motions (SD card required)

TECHNICAL DATA

Electrical data

| Nominal wattage | 15.00 W |
|------------------------|------------|
| Nominal voltage | 220240 V |
| Mains frequency | 5060 Hz |
| Nominal current | 110.000 mA |
| Power factor λ | > 0.5 |
| Protection class | II |

Photometrical data

| Luminous flux | 1000 lm |
|--|------------|
| Total luminous flux of contained light sources | 1400 lm |
| Luminous efficacy | 66 lm/W |
| Color temperature | 3000 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | ≥80 |
| Flickering metric (Pst LM) | - |
| Stroboscope effect metric (SVM) | - |
| Beam angle | 110° |

Dimensions & Weight

| Length | 100.00 mm |
|----------------|-----------|
| Width | 80.00 mm |
| Height | 252.00 mm |
| Product weight | 500.00 g |



Materials & Colors

| Product color | White |
|---------------|-------|
| | White |

| Housing color | White |
|--|--------------------|
| Body material | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|---------------------------|-------------------------|
| Type of connection | Terminal, 2-Pole (L, N) |
| Type of protection | IP44 |
| Dimmable | Yes |
| Type of dimming | WiFi |
| Mounting type | Surface |
| Application environment | Outdoor |
| With light source | Yes |

Lifespan

| Number of switching cycles 12500 | |
|----------------------------------|--|
|----------------------------------|--|

Sensor

| Type of sensor | Motion / Daylight |
|--|-------------------|
| Sensor controlled switching time | 60 s |
| Detection range of motion sensor | 37 m |
| Detection threshold of daylight sensor | 020 lx |

Certificates & Standards

| Standards | CE / UKCA |
|--|-----------------|
| Luminaire with limited surface temperature, "D sign" | No |
| Ball shot safe | No |
| Replaceable light source (EPREL) | Not replaceable |

Additional product data

| Product remark | Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times. |
|----------------|--|
|----------------|--|

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- Mounting screws and dowels included
- SD card not supplied

- Compatible with SD card type (SD/SDHC/SDXC)
- SD Class recommended 120-160MB/s
- Minimum card capacity 8GB/Maximum 128GB

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|--|---------------------------------|
| PDF | User instruction / safety instructions | SMART OUTD WIFI CLOUD CAM |
| PDF | Declarations of conformity | SMART OUTD WIFI CLOUD CAM |
| PDF | Declarations of conformity UKCA | SMART OUTD WIFI CLOUD CAM |
| PDF | Declarations of conformity UKCA | SMART OUTD WIFI CLOUD CAM |
| PDF | EU Data Act | SMART WiFi Lamps and Luminaires |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075763401 | Folding box 1 | 120 mm x 265 mm x 100 mm | 580.00 g | 3.18 dm ³ |
| 4058075763418 | Shipping box 2 | 285 mm x 140 mm x 200 mm | 1375.00 g | 7.98 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/en-int/home-lighting/services/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.