

PRODUCT DATASHEET TR SP HOUSING E GU10 WT

TRACKLIGHT SPOT GU10 | 3-phase tracklight spot with GU10 socket base



Areas of application

- Shops, changing rooms, shop windows
- Hotels, restaurants

Product benefits

- Socket compatible for lamp power up to 10W

Product features

- Base: GU10
- Rotation angle: 350°, tilt angle: 90°
- Durable die-cast aluminum housing
- Available in matt white (like RAL9003), matt black (like RAL9005)



TECHNICAL DATA

Electrical data

| Nominal voltage | 220240 V |
|------------------|----------|
| Mains frequency | 5060 Hz |
| Protection class | П |

Dimensions & Weight

| Diameter | 58.00 mm |
|----------------|-----------|
| Length | 58.00 mm |
| Width | 58.00 mm |
| Height | 145.00 mm |
| Product weight | 151.00 g |



Materials & Colors

| Product color | White |
|--|----------|
| Housing color | White |
| RAL Color (most similar) | RAL 9003 |
| Body material | Aluminum |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C | |
|--|------------------|--|
| Temperature range at storage | -20+80 °C | |
| Type of connection | Adapter, 3-phase | |
| Protection class IK (shock resistance) | IK02 | |
| Dimmable | No | |
| Mounting type | Surface | |
| Mounting location | Mounting track | |

| Application environment | Indoor |
|--------------------------|--------|
| Adjustable | Yes |
| With light source | No |
| Replaceable light source | No |
| Holder designation | GU10 |

Certificates & Standards

| Standards | | CE / UKCA |
|----------------|--------------------------------------|-----------|
| Luminaire with | imited surface temperature, "D sign" | No |
| Ball shot safe | | No |

Additional product data

| Product remark | Available from September 2025 |
|----------------|-------------------------------|
|----------------|-------------------------------|

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

| | Documents and certificates | Document name | |
|-----|--|--|--|
| PDF | User instruction / safety instructions | G11248823 TRACKLIGHT SPOT HOUSING E GU10 | |
| PDF | Legal information | Informationstext 18 Abs 4 ElektroG | |
| PDF | Declarations of conformity | TRACKLIGHT SPOT HOUSING E GU10 | |
| PDF | Declarations of conformity UKCA | TRACKLIGHT SPOT HOUSING E GU10 | |
| | | | |
| | Tender texts | Document name | |
| | Tender documents | TRACKLIGHT SPOT GU10 GU10 WT-en | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume | |
|--------------|------------------------------|--------------------------------------|--------------|--------|--|
|--------------|------------------------------|--------------------------------------|--------------|--------|--|

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854590023 | Folding box 1 | 67 mm x 92 mm x 163 mm | 185.00 g | 1.00 dm ³ |
| 4099854590030 | Shipping box 20 | 385 mm x 350 mm x 190 mm | 4347.00 g | 25.60 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.