

PRODUCT DATASHEET ENDURA® Classic Square Down Rusty

ENDURA® Classic Square | Outdoor Endura Classic square with socket GU10



Areas of application

- Entrance lighting
- Patios, balconies
- Building facades

Product benefits

- High flexibility in the choice of the light source thanks to GU10 socket
- Easy and quick installation
- High-quality materials

Product features

- Die-cast aluminum housing



TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	T .
Operating mode	Mains voltage

Dimensions & Weight

Length	68.00 mm
Width	81.00 mm
Height	92.00 mm
Product weight	300.00 g



Materials & Colors

Product color	Rust
Housing color	Rust
Body material	Aluminum
Cover material	Glass

Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44/IP44
Protection class IK (shock resistance)	IK04
Dimmable	No
Mounting type	Surface
Mounting location	Wall

Application environment	Outdoor
With light source	No
Replaceable light source	No
Holder designation	GU10

Emergency lighting

Type of emergency operation test	None
----------------------------------	------

Certificates & Standards

Standards		CE / UKCA	
Lu	uminaire with limited surface temperature, "D sign"	No	
В	all shot safe	No	

Additional product data

Product remark	Maximum bulb wattage: 35W (7W LED) / Available from January 2026		
Number of illuminants	1		

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

Documents and certificates Document name		Document name	
User instruction / safety instructions		ENDURA CLASSIC SQUARE UP DOWN	
Legal information Safety insert G11219578		Safety insert G11219578	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854712395	Folding box	77 mm x 92 mm x 102 mm	351.00 g	0.72 dm ³
4099854712401	Shipping box 6	245 mm x 110 mm x 232 mm	2287.00 g	6.25 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.