

# PRODUCT DATASHEET DALI Coupler Pushb G2

DALI COUPLER PB G2 | DALI-2 pushbutton coupler to integrate standard switches in DALI systems



#### Areas of application

- Suitable for installation in flush-type boxes
- Individual offices
- Classrooms
- Conference rooms
- Production and assembly facilities

#### Product benefits

- Standard pushbuttons/switches can be used
- DALI-2 certified
- DALI Bus powered (No mains connection necessary)
- Multiple couplers connectable to the same DALI line

#### Product features

- DALI pushbutton coupler
- 4 floating inputs

## TECHNICAL DATA

## Electrical data

Nominal wattage	0.10 W
Nominal voltage	16 V
Mains frequency	0 Hz

## Dimensions & Weight

Length	43.00 mm
Width	43.00 mm
Height	21.00 mm
Product weight	25.00 g

## Colors & materials

Product color	Light grev
1 100001 00101	Light groy

# Temperatures & operating conditions

## Capabilities

Dimmable	No
Dimming interface	DALI-2
Type of installation	Integrated in flush device box

#### Certificates & Standards

Approval marks – approval	CE
Protection class	II
Type of protection	IP20

## DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	DALI COUPLER PUSHB G2	
PDF	Declarations of conformity	Declarations of conformity DALI COUPLER PUSHB G2	
PDF	EU Data Act	Connected Products and Related Software and Services	

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172087575	Folding box	81 mm x 81 mm x 46 mm	42.00 g	0.30 dm <sup>3</sup>
4062172087582	Shipping box 60	344 mm x 254 mm x 278 mm	3187.00 g	24.29 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.